



Solar Off Grid Inverter



MAX 7.2KW-48V

Features

- Customizable status LED bar with RGB lights
- Built-in wifi for mobile monitoring (Android/iOS Apps are available)
- Supports USB On-the-Go function
- Reserved communication port for BMS (RS485, CAN-BUS or RS232)
- Replaceable fan design for ease of maintenance
- Battery independent design
- Configurable AC/PV output usage timer and prioritization
- Selectable high power charging current
- Selectable input voltage range for home appliances and personal computers
- Compatible to Utility Mains or generator input
- Built-in anti-dust kit
- Optional DC output for DC fan, LED bulb, router and so on
- Parallel operation up to 6 units only available





Solar Off Grid Inverter



SPECIFICATIONS

MODEL	MAX 7.2KW-48V
Rated Power	7200VA/7200W
Parallel Capability	up to 6 units

INPUT

Voltage	230 VAC
Selectable Voltage Range	170-280 VAC (For Personal Computers) ; 90-280 VAC (For Home Appliances)
Frequency Range	50 Hz/60 Hz (Auto sensing)

OUTPUT

AC Voltage Regulation (Batt. Mode)	230VAC \pm 5%
Surge Power	15000VA
Efficiency (Peak)	90 % - 93 %
Transfer Time	15 ms (For Personal Computers) ; 20 ms (For Home Appliances)
Waveform	Pure sine wave
No Load Power Consumption	< 70W
Optional DC Voltage	12 VDC \pm 5%, 100W

BATTERY

Battery Voltage	48 VDC
Floating Charge Voltage	54 VDC
Overcharge Protection	66 VDC

SOLAR CHARGER & AC CHARGER

Solar Charger Type	MPPT
Maximum PV Array Power	8000W (4000W x 2)
MPPT Range @ Operating Voltage	90 - 450 VDC
Maximum PV Array Open Circuit Voltage	500 VDC
Maximum Solar Charge Current	80 A
Maximum AC Charge Current	80 A
Maximum Charge Current	80 A

PHYSICAL

Dimension, D x W x H (mm)	147.4 x 432.5 x 553.6
Net Weight (kgs)	18.4
Communication Interface	USB/RS232/RS485/Wifi/Dry-contact

ENVIRONMENT

Humidity	5% to 95% Relative Humidity (Non-condensing)
Operating Temperature	0°C to 55°C
Storage Temperature	-15°C to 60°C

All information contained in this document is subject to change without notice.